



# HIND PROOF NO-2

## PRODUCT DATA SHEET

### RAPID/QUICK SETTING/HARDENING COMPOUND FOR CEMENT MORTAR & CONCRETE

#### DESCRIPTION

Hind Proof No-2 is an extra fast setting waterproofing/plugging compound. It is a pink colored liquid.

#### USES

Hind Proof No-2 is an excellent time tested liquid admixture for emergency/immediate repair work. Instant leak plugging and quick fixing of nozzle. It is widely used as a plugging compound for basements, pipe joins, retaining walls, tunnels and sewage works, where water is pouring under pressure.

#### ADVANTAGES

- Excellent quality plugging compound-consistent performance.
- High early strength- plugging is completed within 5 minutes.
- Simple application
- Excellent adhesion

#### APPLICATION

Cut back the opening of leaking hole to form concave shape tapering to a narrow mouth at the entrance, place the gelled cement mass into the hole and keep the pressure on for 4 to 5 minutes.

#### PROPERTIES

Aspect	Liquid
Specific Gravity	1.25 ± 0.02
Dose	37% by weight of cement. Not to be diluted with water.
Chloride	0.20 % (Max)
Setting Time	30 to 60 seconds.

#### SHELF LIFE

18 months from the date of manufacture. Should be stored in a cool and dry place.

#### PACKING

Available in 1, 5, 20 Kg. HDPE Containers.

#### HANDLING PRECAUTION

Hind Proof No-2 is non-toxic and ingestion is to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice

**Note:**

- Hindcon Chemicals maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products.
- The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.
- Quality of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behavior can change as per the prevailing conditions at the time of applications.
- Since HINDCON CHEMICALS LIMITED has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use.

**HINDCON CHEMICALS LIMITED**

(Formerly HIND SILICATES PVT. LTD.)

(AN ISO 9001: 2008 COMPANY)

**Office**

62B, Braunfeld Row, "VASUDHA", Kolkata - 700027

Tel: 24490835, 24490839. Fax: 24490849

E-mail: [contactus@hindcon.com](mailto:contactus@hindcon.com), [hindconchemicals@yahoo.com](mailto:hindconchemicals@yahoo.com)

**Factory**

Baniyara, Jalan Complex, Gate No.3

Howrah – 711 411. Tel: 2669 9213

[www.hindcon.com](http://www.hindcon.com)